

Luminux is proud to present you the Domino Surface Mount LED downlight which is perfect for indoor and outdoor general lighting and most of commercial and architectural lighting. This unique simple and classic design comes with the cutting edge LED technology and heat dissipation technology. It adopts Multichips-Array LED System (Cree, USA,) technology which can produce up to 2700 lumen with 30W only. The color rendering is up to 84CRI. It is now possible to reduce energy consumption and maintenance costs without compromising on light quality and ambience.

Features

- Simple and Classic Design
- Aluminum Cooling System
- Multichips-Array LED System (Cree, USA)
- High quality reflector with Tempered Glass Cover
- Ultra-easy Installation
- Super Long Life - 70% maintenance of lumen after 50000 hours
- Super High Color Rendering (84 CRI)
- Power factor: >0.90
- Dimming Options: EcoSystem, DALI, 0-10V, TRIAC
- RoHS Compliant
- UV and IR Free



Product Offering

Item	LED Color	Reflector Angle	Finishing	Power Supply	CRI	Watt	Lumen	Note
Domino 170	2700K	38°	<input type="checkbox"/> White	220-240VAC	84	18W	1500	
	3000K	45°	<input type="checkbox"/> Black		90*	25W	2100	
	4000K				30W	2700		
	5000K							

* Optional for CRI90

Application Information

- Indoor General Lighting
- Outdoor General Lighting
- Commercial Lighting
- Architectural Lighting

Dimension

